

AMENDMENTS TO THE CLAIMS

Claim 1 (Currently Amended) An electronic button tag for tagging and identifying cattle comprising a transponder, programmable or not, enclosed in a shell, said shell comprising an open-ended or blind axial transverse passage for a fixing means to the ear of the animal, characterised in that:

the shell is made from two half-shells namely a lower half-shell and an upper half-shell, which are assembled together at a median plane which is disposed transversely to the axial passage opening for the fixing means,

the transponder is fixed in place without compression between the two half-shells using a glue,

the two half-shells are assembled by ~~means of~~ a laser weld.

Claim 2 (Currently Amended) ~~An~~The electronic button tag according to claim 1, ~~characterised in that~~wherein the two half-shells are provided with complementary internal and external walls, contributing to their assembly, to stiffening the shell and to ~~fixing~~ the internal transponder in place.

Claim 3 (Currently Amended) ~~An~~The electronic button tag according to claim 1, ~~characterised in that~~wherein the upper half-shell comprises a sleeve with a central opening around the median axis, wherein a cylindrical wall projects outwards on a planar wall and is extended by an inner cylindrical wall below said planar wall to connect with a corresponding lower cylindrical wall on the lower half-shell, the planar wall of the upper half-shell being connected ion its periphery to a vertical cylindrical wall connecting it to the lower half-shell.

Claim 4 (Currently Amended) ~~An~~The electronic button tag according to claim 3, ~~characterised in that~~wherein the lower half-shell comprises a lower cylindrical inner wall around its median axis corresponding to that of the sleeve of the upper half-shell and providing the transverse passage,

that it is provided with an internal projection,
that it is provided with a projecting peripheral rim cooperating with the
orthogonal peripheral wall of the upper half-shell.

Claim 5 (Currently Amended) ~~An~~The electronic button tag according to
claim 4, ~~characterized in that~~wherein an internal projection is placed between the lower
internal cylindrical wall and the peripheral rim.

Claim 6 (Currently Amended) ~~An~~The electronic button tag according to
claim 4, ~~characterized in that~~wherein the internal projection is of a lesser height than the
clear height within the button tag.

Claim 7 (Currently Amended) An electronic button tag according to claim
3, characterised in that the lower cylindrical ~~wall~~ of the lower half-shell has a conical
form with an upper shoulder enabling the tip of the punch of a male panel tag to be
locked in.

Claim 8 (Currently Amended) ~~An~~The electronic button tag according to
claim 7, ~~characterised in that~~wherein the sleeve is blind on the upper half-shell.

Claim 9 (Currently Amended) ~~An~~The electronic button tag according to
claim 3, ~~characterised in that~~wherein the ends of the vertical walls of the upper half-shell
are provided with flux cores (10).

Claim 10 (Currently Amended) ~~An~~The electronic button tag according to
claim 1, ~~characterised in that~~wherein the processor of the transponder is folded down
onto the coil, the ~~unit~~processor being fixed into position by the glue.

Claim 11 (Currently Amended) ~~An~~The ~~E~~electronic button tag according to
claim 9, ~~characterized in that~~wherein the flux cores are laser welded ~~by use of a laser~~.

Claim 12 (Currently Amended) ~~An~~The electronic button tag according to claim 3, ~~characterised in that~~wherein the lower half-shell is provided with a peripheral rim which on assembly fits into the external shoulder of the vertical wall of the upper half-shell.

Claim 13 (Currently Amended) An electronic button tag for tagging and identifying cattle including a transponder, programmable or not, enclosed in a shell, the shell being composed of a first shell portion and a second shell portion which are assembled together at a median plane, the transponder is fixed in place without compression between the two shell portions using an adhesive and the two shell portions are assembled by means of a laser weld, and the two shell portions are provided with complementary internal and external walls, contributing to their assembly, to stiffen the shell and to fix the internal transponder in place, the second shell portion including a sleeve with a central opening around a median axis, said sleeve is blind and projects outwards from one side of a planar wall and is extended by a cylindrical wall extending from an opposite side of said planar wall to connect with a cylindrical wall of the first shell portion, a planar wall of the first shell portion being connected at its periphery to the second shell portion.

Claim 14 (Currently Amended) ~~An~~The electronic button tag according to claim 13 wherein the cylindrical wall of the first shell portion provides a passage for a punch of a male tag for fixing the tag to the ear of an animal, said cylindrical wall of the first shell portion having a conical form and providing a shoulder within the sleeve to enable a tip of the punch of a male tag to be locked n the sleeve.

Claim 15 (Currently Amended) ~~An~~The electronic button tag as claimed in claim 14, wherein an internal projection is located between the cylindrical wall and a peripheral rim of the second shell position, the internal projection being of a height less than the distance between the planar walls of the first and second shell portions.

Claim 16 (Cancelled)

Claim 17 (Currently Amended) ~~An~~The electronic button tag as claimed in claim 14 or 15, wherein the ends of the cylindrical wall of the second shell portion and a peripheral wall of the second shell portion are provided with flux cores.

Claim 18 (Currently Amended) ~~An~~The electronic button tag according to claim 14 or 15, wherein the ends of the cylindrical wall of the second shell portion and a peripheral wall of the second shell portion are provided with flux cores and the flux cores are laser welded by use of a laser.

Claim 19 (Currently Amended) ~~An~~The electronic button tag according to claim ~~17 or~~ 18, wherein the first shell portion is provided with a peripheral rim which on assembly fits into an external shoulder of the peripheral wall of the second shell portion.

Claim 20 (Currently Amended) ~~An~~The electronic button tag as claimed in claim 13 or 14, wherein a processor of the transponder is located on ~~the a~~ coil, the unit-processor being fixed into position by the adhesive.

Claim 21 (Currently Amended) ~~An~~The electronic button tag as claimed in claim 13, wherein ~~the sleeve is blind,~~ the ends of the cylindrical wall and a peripheral wall of the second shell portion are provided with flux cores and the flux cores are laser welded by use of a laser.

Claim 22 (Currently Amended) ~~An~~The electronic button tag according to claim 21, wherein the first shell portion is provided is with a peripheral rim which on assembly fits into an external shoulder of the peripheral wall of the second shell portion.

Claim 23 (New) An electronic button tag for tagging and identifying cattle comprising:

a transponder, programmable or not, enclosed in a shell, the shell is made from two half-shells namely a lower half-shell and an upper half-shell, which are assembled together at a median plane which is disposed transversely to the axial passage opening for the fixing means, the two half-shells are provided with complementary internal and external walls, contributing to their assembly, to stiffen the shell and to fix the internal transponder in place, the upper half-shell has a sleeve with a central opening around the median axis forming an open-ended or blind axial passage for a fixing means to the ear of an animal, wherein a cylindrical wall below said planar wall to connect with a corresponding lower cylindrical wall on the lower half-shell, the planar wall of the upper half shell being connected on its periphery to a vertical cylindrical wall connecting it to the lower half-shell, the transponder is fixed in place without compression between the two half-shells using a glue, the two half-shells are assembled by means of a laser weld.

Claim 24 (New) The electronic button tag according to claim 23, wherein the lower cylindrical wall is provided with an internal projection that is provided with a projecting peripheral rim cooperating with an orthogonal peripheral wall of the upper half-shell.

Claim 25 (New) The electronic button tag according to claim 24, wherein an internal projection is placed between the lower cylindrical wall and the peripheral rim.

Claim 26 (New) The electronic button tag according to claim 24, wherein the internal projection is of a lesser height than a clear height within the button tag.

Claim 27 (New) The electronic button tag according to claim 23, wherein the lower cylindrical wall has a conical form with an upper shoulder enabling a tip of a punch of a male panel tag to be locked in.

Claim 28 (New) The electronic button tag according to claim 23, wherein ends of the vertical walls of the upper half-shell are provided with flux cores.

Claim 29 (New) The electronic button tag according to claim 23, wherein a processor of the transponder is folded down onto the coil, the processor being fixed into position by the glue.

Claim 30 (New) The electronic button tag according to claim 28, wherein the flux cores are laser welded.